


OPERATING INSTRUCTIONS


ALE-EL41ME10B / ALE-EL42ME10B

A. Seat height adjustment the chair while lifting the lever (A) under seat height, lift the lever (A) while sitting the right side of the seat. To lower the To raise the seat height, stand up from




Seat angle adjustment lock the chair seat in the upright or vertical Push the lever (B) upward. Leaning back will position, sit upright and push the lever (B) cause the chair seat to tilt backwards. To

œ



C. Back angle adjustment

cause the chair back to tilt backwards. To lock the chair back in the upright or vertical Push the lever (C) upward. Leaning back will position, sit upright and push the lever (C) downward.



H. Sliding seat adjustment

to lock in desired seat position. Pull handle out to allow seat to slide forward or backward. Release handle

J. Backrest height adjustment

F. Arm width adjustment

G. Arm height adjustment


on the outside of each arm and move


To adjust arm height, push the button the arm up or down. Release the button


to set the height.

under the arm support and move arm to To adjust the arm width, loosen the bolt the desired placement. After reaching desired placement, tighten bolt

until it clicks into the desired height. To raise the back, pull up on the seat back back up to desired position. then lower all the way down. Raise the way up until tension is released and To lower the back, raise the seat back all







AT LEAST EVERY THREE MONTHS, CHECK ALL BOLTS, DO NOT SIT ON ANY PART OF THE CHAIR EXCEPT THE SEAT DO NOT USE CHAIR ON UNEVEN FLOOR SURFACES DO NOT USE THIS CHAIR AS A STEP STOOL / LADDER DO NOT USE CHAIR UNLESS ALL BOLTS, SCREWS AND KNOBS ARE TIGHTENED.

- SCREWS AND KNOBS TO BE SURE THEY ARE TIGHTENED.
- IF ANY PARTS ARE MISSING, BROKEN, DAMAGED OR WORN
- FAILURE TO FOLLOW THESE WARNINGS COULD RESULT IN SERIOUS INJURY


D. Forward tilt lever

and pull lever (D) backward. This will allow you to lean to a

To activate the forward tilt, lift the lever (B), lean back slightly

E. Tilt tension lever (B) downward to lock position. Knob underneath seat adjusts angle and ease with which chair forward position. Once the desired angle is reached, push To increase tension, turn knob to the right. To release tension reclines to the different weights and strengths of different users

(loosen), turn knob to the left.



PREVENTIVE MAINTENANCE AND WARNING!

USE THIS PRODUCT ONLY FOR SEATING ONE PERSON AT A TIME

